





MAIN COMPONENTS

- Compressor unit:** The unit should be installed on a level floor suitable for taking the weight of the compressor.
- Compressed air outlet valve.
- Delivery pipe:**
The max. total pipe length can be calculated from: $L = \frac{\Delta P \times d^5 \times P}{450 \times Q_c^{1,85}}$
L is the length of the pipe (m)
 ΔP is the max. allowable pressure drop (recommended 0,1 bar)
d is the inner diameter of the pipe (mm)
P is the absolute pressure at the compressor outlet (bar)
Qc is the compressor FAD (l/s)
- Ventilation:**
The inlet grid(s) and ventilation fan should be installed in such a way that any recirculation of hot cooling air to the inlet gratings of the compressor/dryer is avoided.
The air velocity to the grid(s) has to be limited to 5m/s.
Maximum allowable pressure drop over cooling air ducts is 50 Pa.
When 50 Pa is exceeded, a ventilation fan is needed at the outlet of the cooling air ducts.
The maximum air temperature at the compressor intake opening is 40°C, min. 0°C.
Alternative 1 and 3: The required ventilation to limit the compressor room temperature can be calculated from : $Q_v = 0,92 N / \Delta T$
Qv is the required ventilation capacity (m³/s)
N is the nominal motor power of the compressor (kW)
 ΔT is the compressor room temperature over the outdoor temperature (°C)
Alternative 2 and 4: The fan capacity should match the compressor-fan capacity at a pressure head equal to the pressure drop caused by the cooling air ducts.
- Control cubicle with monitoring panel.
- Mains cable entry.
- Filter type DD for general purpose filtration (particle removal down to 1 micron).
A high efficiency PD- filter may be installed downstream the DD- filter (particle removal down to 0,01 micron).
Should odeurs be undesirable, a QD active carbon filter should be installed after the PD -filter.
It is recommended to install by-pass pipes over each filter together with ball valves in order to isolate the filters during service operations, without disturbing the compressed air delivery.
- Safety valve.
- The drain pipes to the drain must not dip into the water.
- Compressor element cooling air outlet.
- Canopy ventilation outlet.
- Aftercooler and dryer cooling air outlet.
- Data-plate.

VENTILATION PROPOSALS



- Notes :
- All pipes should be installed stress-free to the compressor unit.
 - For more information concerning air nets, cooling systems, etc refer to the compressor installation manual.
 - For dimensions and air flow directions refer to the AHB dimension drawings.

Tolerances, if not indicated, according to:							
ATLAS COPCO STANDARD CLASS							
Name	DIMENS. INSTALL.			SF15+22+		Confidentiality Class acc. to 1102 K	
Material	NOT APPLICABLE					3	
Treatment	Not Applicable					INV	
		Scale 1:20	Family	A1	Compare	Drawing owner	
		Drawn by mpoalbh	Blank nr.		Replaces	All	
STATUS	Version Drwg 00.01	Blank wt.	0 Kg	Finl wt. 12270,817 Kg	Designation	Sheet 1 / 1	
Approved	Des checked.	Prod checked.	Approved.	Date 2013-10-12	9820737200		

9820737200

00.01

Ed . Version 3D

Approved

00			2014-08-05		All materials supplied are in compliance with the requirements of the List of Prohibited Substances
Ed	Position	Modified from	Date	Intr./Appd.	

CONFIDENTIAL:
This document is our property and shall not be distributed or used without our permission. It is intended for internal use only and shall not be used for any other purpose.